

Manufacturer Info...

MFR Information (Manufacturer Information)

MFR_ID (2 bytes)

2-byte programmable

MFR_MODEL (5 bytes)

5-byte programmable i.e partnumber in ASCII format

MFR_LOCATION (1 bytes)

1-byte programmable

MFR_REVISION (1 bytes)

1-byte programmable

MFR_DATE (4 bytes)

Reserved by Infineon for storing vendor log data

MFR_SERIAL (4 bytes)

Reserved by Infineon for storing vendor log data

	HEX	ASCII
MFR_ID (2 bytes)	4952	IR
MFR_MODEL (5 bytes)	0000000000	
MFR_LOCATION (1 bytes)	00	
MFR_REVISION (1 byte)	00	
MFR_DATE (4 bytes)		00000000
MFR_SERIAL (4 bytes)		00000000

User Data	
User Data 0 (2 bytes)	0000
User Data 1 (2 bytes)	0000

Checksum	
Register (MCFG_EN = 0)	512BD25A
Register (MCFG_EN = 1)	2BD4070C
NVM	

User Data

memory location where a User can store any data.

Checksum

Register : Displays the cyclic redundancy code value calculated by PowerClient based on the current register values

NVM (permanent memory in device): Displays the cyclic redundancy code value calculated by the device during download